

PTZ-KEYB 3 Axis PTZ Controller/Keyboard



INFO:

- 3 Axis joystick for simultaneous Pan/Tilt/Zoom movement
- Variable Speed Control for Pan/Tilt Movement
- Control 1-255 PTZ cameras
- Multiple Controlling Protocol Over Rs485/Rs232
- TX: 3 ports, TRX: 1 port
- Program PTZ actions: Preset, Tour, Pattern, etc.
- DVR interface / USB mouse function
- Large Backlight LCD for Clear Overview and Menu Setup
- User password support
- Programmable transmission speed for each ID. (2.4-57.6kbps)
- DC12V or 9V battery for field test

SPECIFICATIONS:

FUNCTION	
Interface	RS-485 / RS-422
Ports	3 TX ports, 1 TRX port, 1 USB-B
Operating Distance	4,000ft (24 AWG wire)
Protocol	Clinton, Pelco-D, Pelco-P, WTX, EZP, etc..)
Baudrate	2400 / 4800 / 9600 / 19200 / 38400 / 57600
Connector Type	Terminal Block (8p)
Joystick	3 Axis, variable speed with zoom
LCD Display	Backlight, 16 Character x2 Lines
GENERAL	
Power Requirement	DC12V or 9V battery (Battery Mode)
Power Consumption	140mA (Max.)
Operating Temperature	23°F - 104°F / -5°C - 40°C
Operating Humidity	0-70% (No Condensation)
Material	Plastic housing with Rubber buttons
Dimensions (L x W x H)	11" x 7" x 4" 280mm x 179.5mm x 100mm
Weight	1.5 lbs / 0.7 kg

DIMENSIONS:

