



CW1000 / CB1000 RG-59 & 18-2 Combo Cable



▲
CW1000



▲
CB1000

INFO:

- 1000' Spool
- 95% Shielding
- Solid Copper Core
- Sequential Length Markers
- Siamese Zip Type Cable
- UL Listed

CW1000 (White)
CB1000 (Black)

SPECIFICATIONS:

Description	RG-59 / U, 20AWG / Power 18-2, 18AWG	
Length	1,000'	
Dielectric	Gas Injected Foam PE	
Conductor / Shielding	Bare Copper / 95% coverage	
Jacket	75° PVC U/V White *CW1000 75° PVC U/V Black *CB1000	
Nom. Imp. Ω	75	
Vel. of Prop.	82%	
Nominal Attenuation	Mhz	dB/1,000'
	1	.33
	10	.88
	50	1.85
	100	2.51
	200	3.58
	400	5.29
	700	7.45
	900	8.7
	1,000	9.31

RG59-1000 Black Rg-59 Coax Cable



INFO:

- 1000' Spool
- 95% Shielding
- Solid Copper Core
- Sequential Length Markers
- UL Listed

SPECIFICATIONS:

Description	RG-59 / U, 20AWG	
Length	1,000'	
Dielectric	Gas Injected Foam PE	
Conductor / Shielding	Bare Copper / 95% coverage	
Jacket	75° PVC U/V Black	
Nom. Imp. Ω	75	
Vel. of Prop.	82%	
Nominal Attenuation	Mhz	dB/1,000'
	1	.33
	10	.88
	50	1.85
	100	2.51
	200	3.58
	400	5.29
	700	7.45
	900	8.7
	1,000	9.31