# **clinton**electronics

# **CE-IDXOHD(B)L** HD-SDI / EX-SDI Indoor Dome Camera




## INFO:


· 1/2.9" SONY 2.12 Megapixel CMOS Sensor

wdr15

- · Full HD 1080p Resolution
- HD Over Coax Cable (HD-SDI & EX-SDI)
- · 4mm (f2.6) Fixed Lens
- · EXHD Digital Signal Processor
- $\cdot\,$  OSD Menu Control via Built-in Joystick on cable
- Mounts to: Single Gang, Double Gang, 3-1/4" & 3-1/2", or 4" Oct/Rd Conduit Boxes
- · 3 Axis Adjustment
- · DC12V
- $\cdot$  UL Listed

#### **DIMENSIONS:**





# SPECIFICATIONS:

Camera	
Image Sensor	1/2.9" SONY 2.12 Megapixel CMOS Sensor
Resolution	Full HD 1080p
Effective Pixels	1944 (H) x 1092 (V)
Scanning System	Progressive Scan
S/N Ratio	More than 52dB (AGC Off)
Frame Rate	1080p_30 / 720p_30 (15fps w/ WDR On)
Minimum Illumination	1 Lux (COLOR) w/ Sens-Up @ x32 0.1 Lux (B&W) w/ Sens-Up @ x32
Shutter Speed	1/30 ~ 1/60,000 sec, / AUTO
Lens	4mm (f2.6) Lens
Filed of View	75° (Horizontal)
Video Output	1 HD-SDI/EX-SDI Output, 1 Analog Output
Power Consumption	100mA (DC12V)
Power Requirement	DC12V
Operating Temperature	32°F ~1 13°F / 0°C ~ 45°C
Operating Humidity	90% RH Max.
Weather Rating	N/A
IR LEDs	N/A
Heaters/Fan	N/A
Materials	Plastic Case w/Polycarbonate Dome
Dimensions	4.80" (Dia.) x 3.70" (H) / 121.9mm (Dia.) x 93.9mm(H)
Weight	0.60 lbs / 0.27g
OSD	
DSP Type	EXHD - Lite
Menu Control	OSD Menu Control via Built-In Joystick or CE-REMOTE
Exposure	Brightness, Shutter, Sens-Up, AGC
Sens-Up	Auto (x2 ~ x32)
White Balance	AWB, ATW, AWC-Set, Manual
Digital Dynamic Range	WDR (Digital), ACE (Adaptive Color Enhancement)
Backlight Control	HLC, BLC
Day/Night	Auto, Color, B/W, External
Noise Reduction	3DNR (Low, Middle, High)
Smart IR	Anti-Sat
Camera Title/ID	Yes (Up to 8 Characters)
Motion Detection	4 Areas
Privacy Masking	24 Zones (16 Box / 8 Polygon)
Digital Effects	Mirror, Flip, D-Zoom (1X-16X), Defog
Mode Select	HD-SDI, EX-SDI
Frame Rate	720p (30 fps), 1080p (30 fps)
Languages	English, Japanese, Chinese, Korean
Other	Sharpness, Color Gain, Gamma, COM. (Cam ID / Baud Rate), Freq (50Hz / 60Hz), Shading, CVBS Filter

ACCESSORIES	
CE-IDXWB (White)	Wall Bracket for IDX Series Cameras
CE-IDXPC (White)	Pendant Cap for IDX Series Cameras
CE-IDXDPC (White)	Deep Pendant Cap for IDX Series Cameras
CE-IDXWBB (Black)	Wall Bracket for IDX Series Cameras
CE-IDXPCB (Black)	Pendant Cap for IDX Series Cameras
CE-IDXDPCB (Black)	Deep Pendant Cap for IDX Series Cameras

### CERTIFICATIONS:









clintonelectronics | 6701 Clinton Road Loves Park, IL 61111 | 800.447.3306 | @clintonelec | www.clintonelectronics.com | 05-20-16

Clinton reserves the right, without notification, to make changes in product design & specification.