

CE-M24-SS

24" Stainless Steel Public View Monitor



KEY FEATURES:

- Waterproof NEMA 4 Stainless Steel Enclosure built to withstand rain, snow, dust, and being directly sprayed with a hose
- Sunlight-Readable HD Monitor; designed to operate in direct bright sunlight, or in other high ambient-light conditions
- 1,000 nit Brightness / 5,000:1 Contrast Ratio
- Protective Anti-Reflective Glass Front
- Built-In Full HD 1080p EX-SDI Camera
- 3-10.5mm (f1.4) Motorized True D/N Auto Focus Zoom Lens
- Weatherproof, removable cover protects power & video connections
- 1 HDMI Input
- 1 BNC Analog Input / 1 BNC Analog Output
- 1 EX-SDI/HD-SDI Output
- SD Card Player for PIP Window (4GB SD Card Included)
- Temperature controlled enclosure with built-in fan
- Flashing LEDs
- Text Overlay "RECORDING IN PROGRESS" or "WELCOME" in English or Spanish
- VESA 100
- DC24V
- UL Listed

MONITOR	
Display	24" LED Backlight LCD
Resolution	1920 x 1080
Aspect Ratio	16:9 (True 16:9 Camera Image)
Display Colors	16.7M (8 BIT)
Brightness	1,000 nit
Contrast Ratio	5000:1
Viewing Angle (H x V)	178° x 178°
Response Time	25ms
Mounting	VESA 100
In / Out Impedance	75Ω / Auto Terminating Output
Video Inputs / Outputs	1 HDMI Input 1 EX-SDI / HD-SDI Output 1 BNC (Analog) Input 1 BNC (Analog) Output
Certifications	UL Listed, FCC, CE, RoHS
Power Consumption	45 Watts
Power Requirement	DC24V
Operating Temperature	-4°F - 158°F / -20°C - 70°C
Dimensions (W x H x D)	24" x 16.75" x 3.25" 609.96mm x 425.45mm x 82.55mm
Weight	28.8 lbs / 13.06 kgs

CAMERA	
Image Sensor	1/3" Panasonic 2.48 Megapixel CMOS Image Sensor
Resolution	Full HD 1080p @ 30fps
Effective Pixels	1920 (H) x 1080 (V)
Minimum Illumination	0.1 Lux Color / 0.01 LUX B&W
Shutter Speed	1/50 - 1/10,000 sec.
Lens	3-10.5mm (f1.4) Motorized True D/N Auto Focus Zoom Lens

RECOMMENDED POWER SUPPLY	
CE-PS200	120W Single Monitor Power Supply (24VDC)
CE-S320-B	320W Multiple Monitor Power Supply (24VDC)
CE-600-24-B	600W Multiple Monitor Power Supply (24VDC)

DIMENSIONS:

