

## CE-LCD7-TEST

7" Multi-Format CCTV Test Monitor



DISPLAY	
LCD Panel	7" TFT-LCD, backlight LED
Resolution	1280x800 WXGA 16:10
Brightness	400 nit
Viewing Angle	89° (H) / 89° (V)
Response Time	11ms
VIDEO INPUT	
SDI	HD-SDI, EX-SDI, EX-SDI 2.0, EX-SDI 4MP (auto detects)
Analog	CVBS, HD-Analog: CVI, TVI, AHD
HDMI	max 1920x1080p @ 60fps
VGA	max 1600x1200
MISC INPUT	
Audio	In/Out (3.5Ø Earphone Jack)
RS-485	(+/-), Multiple Protocols supported
POWER	
Battery Type	Li-Ion Battery - rechargeable
Battery Voltage	11.1V (working), 12.6V (peak)
Battery Capacity	5460mAh (60.61Wh)
Battery Life	6-8 hours w/ 100% charge
Power Output	DC12V (500mA)
GENERAL	
Operating Temperature	32°F - 122°F / 0°C - 50°C
Operating Humidity	0-80% RH
Dimensions (L x W x H)	9.45" x 6.03" x 1.96" / 241mm x 153.4mm x 50mm
Weight	3.35 lbs / 1.51 kg

### Key Features:

- 7" High resolution, LED backlight screen
- Compatible with most CCTV signal types:
  - SDI Input (HD-SDI, EX-SDI, EX-SDI 2.0, EX-SDI 4MP)
  - Analog Input (CVBS, HD-Analog: CVI, TVI, AHD)
  - HDMI Input
  - VGA Input
- RS-485 (+/-) for testing PTZs
- Audio In/Out
- DC12V Power Output for testing cameras
- Supports EX-SDI 2.0 UCC (Up the Coax Communication)
- Built-in Signal Level Meter for HD-SDI, EX-SDI, EX-SDI 2.0
- Rechargeable Li-Ion Battery, charger included
- Includes protective carrying bag, neck strap, DC12V male-to-male cable, DC12V pig-tail, and 3ft coax test cable

### Dimensions:

Unit : Inches

