

## CE-S320-B

DC24V (12.5 Amp) 3 PVM Power Supply



### KEY FEATURES:

- DC24V, 12.5 Amps
- 320 Watt Output
- 3 Pigtail (+/-) DC24V Outputs
- Adjustable Voltage from DC 20-27V
- Short Circuit, Overload, Over Voltage, and Temperature Protection
- Truss Mount, 19" Rack Mount, & Wall Mount
- Recommended for all Clinton DC24V LCDs or PVMs
- UL Listed

POWER	
Input Voltage	88 - 132VAC / 176 - 264VAC (selectable by switch)
Output Voltage	DC24V
Total Outputs	3 Ch (+/- pigtail with butt-splice connectors)
Total Amps	12.5 Amps
AC Inrush Current	20A @ 115VAC, 40A @ 230VAC (cold start)
DC Adjustment Range	+/-10% rated output voltage
Overload Protection	105% - 135% rated hiccup mode, auto-recovery
Over Voltage Protection	115% - 145% rated output voltage
Fuse	5A glass
Setup, Rise, Hold Up Time	2000ms, 20ms, 20ms @ full load & 230VAC
Withstand Voltage	I/P-O/P: 3.0KVAC, I/P-FG:1.5KVAC, 1 minute

GENERAL	
Materials	Steel Enclosure
Certifications	UL Listed, FCC, CE
Operating Temperature	32°F - 104°F / 0°C - 40°C
Dimensions	19" (W) x 5" (D) x 3.5" (H) 484.6mm (L) x 127mm (W) x 88.9mm (H)
Weight	9.4 lbs / 4.26 kgs

### ASSEMBLY:

