

CE-S600-24-B

DC24V (25 Amp) 3 PVM Power Supply



KEY FEATURES:

- DC24V, 25 Amps
- 600 Watt Output
- 3 Terminal Block DC24V Outputs
- Adjustable Voltage from DC 20-27V
- Short Circuit, Overload, Over Voltage, and Temperature Protection
- Truss Mount, 19" Rack Mount, & Wall Mount
- Recommended for all Clinton DC24V LCDs or PVMs
- UL Listed Components

POWER	
Input Voltage	88 - 132VAC / 176 - 264VAC (selectable by switch)
Output Voltage	DC24V
Total Outputs	3 Ch (+/- pigtail with butt-splice connectors)
Total Amps	25 Amps
AC Inrush Current	20A @ 115VAC, 40A @ 230VAC (cold start)
DC Adjustment Range	+/-10% rated output voltage
Overload Protection	105% - 135% rated hiccup mode, auto-recovery
Over Voltage Protection	115% - 145% rated output voltage
Fuse	5A glass
Setup, Rise, Hold Up Time	1000ms, 50ms, 14ms @ full load
Withstand Voltage	I/P-O/P: 3.0KVAC, I/P-FG:1.5KVAC, 1 minute

GENERAL	
Materials	Steel Enclosure
Certifications	UL Listed, FCC, CE
Operating Temperature	32°F - 104°F / 0°C - 40°C
Dimensions	19" (W) x 5" (D) x 3.5" (H) 484.6mm (L) x 127mm (W) x 88.9mm (H)
Weight	11.2 lbs / 5.08 kgs

ASSEMBLY:

